

AXIS FA51 Main Unit

Single-channel main unit with HDMI output

This modular single-channel main unit can connect to one sensor unit offering highly discreet surveillance. Featuring an HDMI output, it's possible to display live video on a public viewing monitor. And, AXIS Face Detector highlights faces within bounding boxes to let would-be shoplifters know they're being monitored and proactively reduce shoplifting. Compatible with all AXIS FA sensor units including IR sensor units, you'll enjoy excellent video quality even in complete darkness. Furthermore, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis devices on your network.

- > **HDTV 1080p at full frame rate**
- > **AXIS Face Detector preinstalled**
- > **HDMI output for public viewing monitors**
- > **1 configurable input/output port**
- > **Compatible with all AXIS FA sensor units**



AXIS FA51 Main Unit

System on chip (SoC)		Network security	IEEE 802.1X (EAP-TLS) ^a , IEEE 802.1AR, HTTPS/HSTS ^a , TLS v1.2/v1.3 ^a , Network Time Security (NTS), X.509 Certificate PKI, IP address filtering
Model	ARTPEC-6	Documentation	<i>AXIS OS Hardening Guide</i> <i>Axis Vulnerability Management Policy</i> <i>Axis Security Development Model</i> To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity
Memory	1024 MB RAM, 512 MB Flash	General	
Video		Casing	IP4X- Aluminum casing Color: black NCS S 9000-N
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	Sustainability	PVC free, BFR/CFR free
Resolution	1920x1080 (1080p) to 160x90	Power	Power over Ethernet (PoE) IEEE 802.3af Type 1 Class 3, typical 5.2 W, max 6.82 W
WDR	Forensic WDR	Connectors	RJ45 10BASE-T/100BASE-TX PoE RJ12 for sensor unit 4-pin terminal block for two configurable alarm inputs/outputs (12 V DC output, max. load 50 mA) HDMI type D
Frame rate	Up to 25/30 fps in all resolutions	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264 HDMI	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Maximum temperature (intermittent): 60 °C (140 °F) Start-up temperature: -20 °C (-4 °F) Humidity 10–85% RH (non-condensing)
HDMI output	Single camera source Playlist: single camera sources, still images 1080p 30/25/24 fps (50/60 Hz) 720p 50/60 fps (50/60 Hz) 576p 50 fps (50/60 Hz) 480p 60 fps (50/60 Hz)	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–85% RH (non-condensing)
Image settings	Contrast, brightness, sharpness, white balance, exposure control, exposure zones, compression, rotation: 0°, 90°, 180°, 270° including corridor format, mirroring, polygon privacy mask, control queue	Approvals	EMC EN 55035, EN 55032 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IS 13252 Environment IEC/EN 60529 IP4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267
Pan/Tilt/Zoom	Digital PTZ, preset positions	Dimensions	24 x 49 x 152 mm (0.9 x 1.9 x 6.0 in)
Network		Weight	195 g (0.43 lb)
Security	IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, multi-level user, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified)	Included accessories	Installation guide, Windows [®] decoder 1-user license, terminal block connector
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS ^a , TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, RTCP, DHCP, SSH, CDP, MQTT, Syslog, Link-Local address (ZeroConf)	Optional accessories	AXIS T8415 Wireless Installation Tool, AXIS Surveillance Cards, AXIS T8120 Midspan 15 W 1-port For more accessories, see axis.com
System integration		Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF [®] Profile G, ONVIF [®] Profile M, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Event conditions	Device status, edge storage, I/O, PTZ, scheduled event, video MQTT subscribe	Warranty	5-year warranty, see axis.com/warranty
Event actions	Toggle I/O, send images, publish MQTT, send notifications, overlay text, recordings, SNMP trap messages, status LED, video clips MQTT publish	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>	
Data streaming	Event data	Environmental responsibility: axis.com/environmental-responsibility	
Analytics			
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, AXIS Face Detector, active tampering alarm Supported AXIS People Counter, autotracking Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap		
Cybersecurity			
Edge security	Software: Signed firmware, brute force delay protection, digest authentication, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Secure boot, Axis Edge Vault with Axis device ID, signed video, secure keystore (CC EAL4+ certified hardware protection of cryptographic operations and keys)		